

VISOR® V10 Object Standard, medium field of view

Vision sensor for object detection, simple presence and completeness checks





PRODUCT HIGHLIGHTS

- User-friendly configuration and viewer software with hierarchical user rights
- Detectors for object detection
- Efficient part detection and tracking
- Precise position determination: X/Y-position and orientation
- Comprehensive logic functions for digital switching outputs

Optical data		Functions	
Resolution	800 x 600 Pixel	Number of jobs / detectors	8 / 32
Imaging chip CMOS	1/3.6", monochrome / color	Detectors	Position tracking: X/Y and orientation; Pattern matching / Contour: teach-in and detection of patterns and contours;
Integrated lens, focal length [mm]	9.6 (medium)		Grey threshold, Brightness: evaluation of brightness;
Pixel size	4.8 µm x 4.8 µm		Contrast: evaluation of contrast;
Focus	Motorized		Color area²: area inspection of colors, with selectable tolerance;
Adjustment range	12 mm to infinity		
Integrated illumination	White (5000 K), red (635 nm) ¹ , infrared (850 nm) ¹ LEDs		
Minimum field of view, X x Y	7 x 3 mm		
Electrical data		Mechanical data	
Operating voltage, +U _B	18 ... 30 DC ³	Dimensions	70.4 x 45 x 45 mm (without plug)
Current consumption (without I/O)	≤ 300 mA	Enclosure rating	IP 67 & IP 65
Protective circuits	Reverse-polarity protection, U _B / short-circuit protection of all outputs	Material, housing	Aluminium, die-cast, RoHS compliant
Power On Delay	Approx. 13 s after Power on	Material, front screen	Plastic
Outputs	PNP/NPN (switchable)	Ambient temperature: operation	0 ... +50 °C ⁴
Max. output current (per output)	50 mA, 100 mA (pin 12)	Ambient temperature: storage	-20 ... +60 °C ⁴
Switching threshold inputs incl. encoder	PNP/NPN High > U _B -1 V / Low < 3 V	Weight	Approx. 200 g
Input resistance	> 20 kΩ	Plug connections	Supply and I/O M12, 12-pin Ethernet M12, 4-pin
Interfaces	Ethernet (LAN), EtherNet/IP, PROFINET, SensoWeb	Vibration resistance	EN 60068-2-6
Inputs/outputs	2 inputs, 2 outputs, 4 selectable inputs/outputs	Shock resistance	EN 60068-2-27
Encoder	No		

¹ Not Color hardware ² Color hardware ³ Max. ripple < 5V_{SS} ⁴ 80 % air humidity, noncondensing



- Increased depth of field
- Normal depth of field

Illumination	Part number	Article number	Accessories	
White	V10-OB-S3-W-M-M2	631-91044	Connection cables	From Page A-38
Red	V10-OB-S3-R-M-M2	631-91046	Illumination	From Page A-27
Infrared	V10-OB-S3-I-M-M2	631-91048	Brackets	From Page A-4
White	V10C-OB-S3-W-M-M2	631-91050	Interface accessories	From Page A-38