

IS 455

Inductive sensor in cubic housing



Sensor data		Functions		
Switching distance Repeatability Hysteresis Reduction factor, Al Reduction factor, Cu Reduction factor, V2A Reduction factor, steel FE 360 Reduction factor, brass	$ \begin{array}{c c} 0.8 \text{ mm} \\ \hline 0.01 \text{ mm}^{1} \\ \leq 10 \%^{2} \\ \hline 0.60 \\ \hline 0.60 \\ \hline 0.85 \\ \hline 1.00 \\ \hline 0.70 \\ \hline \end{array} $	Indicator LED, yellow	Switching output indicator	
Electrical data		Mechanical data		
Electrical data		Mechanical data		
Operating voltage, +U _B	10 30V DC ³	Mechanical data Dimensions	5 x 5 x 25 mm	
	10 30V DC ³ ≤ 10 mA		5 x 5 x 25 mm Flush	
Operating voltage, +U _g No-load current, I _o		Dimensions		
Operating voltage, +U _B No-load current, I ₀ Output current, Ie	≤ 10 mA	Dimensions Mounting	Flush	
Operating voltage, +U _B No-load current, I ₀ Output current, Ie Voltage drop, U _D	≤ 10 mA ≤ 200 mA ≤ 2V at 200 mA Reverse-polarity protection, U _B / short-cir-	Dimensions Mounting Enclosure rating	Flush IP 67 ⁴	
Operating voltage, +U _B No-load current, I ₀ Output current, Ie Voltage drop, U _D	≤ 10 mA ≤ 200 mA ≤ 2 V at 200 mA	Dimensions Mounting Enclosure rating Material, housing	Flush IP 67 ⁴ Brass, chrome-plated	
Operating voltage, +U _B No-load current, I ₀ Output current, Ie Voltage drop, U _D Protective circuits	≤ 10 mA ≤ 200 mA ≤ 2V at 200 mA Reverse-polarity protection, U _B / short-cir-	Dimensions Mounting Enclosure rating Material, housing Material, front surface	Flush IP 67 ⁴ Brass, chrome-plated Polyester	
Operating voltage, +U _B	 ≤ 10 mA ≤ 200 mA ≤ 2 V at 200 mA Reverse-polarity protection, U_B / short-circuit protection (Q) / induction protection 	Dimensions Mounting Enclosure rating Material, housing Material, front surface Type of connection	Flush IP 67 ⁴ Brass, chrome-plated Polyester See Selection Table	

¹ U_B = 20 ... 30 V DC, T_A = 23 °C ± 5 °C ² Refers to switching distance ³ Max. 20 % ripple, within U_B ⁴ With connected IP 67 plug



Switching distance	Switching output	Type of connection	Part number	Article number
0.8 mm	PNP	Cable, 2m, 3-wire	IS 455-02	996-50585
0.8 mm	NPN	Cable, 2m, 3-wire	IS 455-01	996-50607