

TECPEL

Digital Clamp-on Meters

1000A AC Amp + 2000M Ω



DCM-2600

- ☐ 3 1/2 Digit display
- ☐ AC current up to 1000A
- ☐ AC voltage up to 750V
- ☐ DC voltage up to 1000V
- ☐ Resistance up to 2000M Ω
- ☐ Display hold function
- ☐ Audible continuity test
- ☐ Overrange indication
- ☐ Maximum recording mode
- ☐ Confirm to the IEC-1010-1,
- ☐ UL1244/UL3111, CE standard
- ☐ Hand guard protection
- ☐ Carrying case

DC voltage ranges	1000V, $\pm$ (0.5%+1dgt)
AC voltage ranges	750V, $\pm$ (1.2%+4dgt)
AC current ranges	200A, 1000A, $\pm$ (1.5%+5dgt)
Resistance ranges	200 Ω , 20K Ω , 20M Ω , 2000M Ω , $\pm$ (1%+3dgt)
Continuity test	Audible indication 200 Ω , threshold <75 Ω
General	
Power requirement	9V Battery x1
Dimension	275x90x43mm (10.8"x3.6"x1.7")
Weight	17 oz(482g)
Accessories	Test leads, soft carrying case, battery and owners manual.

conductor jaw size : 57mm

1000A AC/DC Amp + Frequency



DCM-2605

- ☐ 3 1/2 Digit display
- ☐ AC/DC current up to 1000A
- ☐ AC voltage up to 750V
- ☐ DC voltage up to 1000V
- ☐ Resistance up to 200K Ω
- ☐ Frequency up to 40KHz
- ☐ Display hold function
- ☐ Audible continuity test
- ☐ Overrange indication
- ☐ Maximum recording mode
- ☐ Confirm to the IEC-1010-1
- ☐ UL 1244/UL3111, CE standard
- ☐ Hand guard protection
- ☐ Carrying case

DC voltage ranges	1000V, $\pm$ (0.5%+1dgt)
AC voltage ranges	200V, 750V, $\pm$ (1.5%+4dgt)
AC current ranges	200A, 1000A $\pm$ (1.5%+5dgt)
DC current ranges	200A, 1000A $\pm$ (1.5%+5dgt)
Resistance range	200 Ω , 200K Ω $\pm$ (1.0%+3dgt)
Continuity test	Audible indication less than 30 Ω
General	
Power requirement	9V Battery x1
Dimension	277x102x49mm (10.9"x4.0"x1.9")
Weight	18.9 oz(540g)
Accessories	Test leads, soft carrying case, battery and owner manual.

conductor jaw size : 57mm

1000 Amp AC/DC + TRUE-RMS



DCM-2606

- ☐ 3 3/4 Digit display with bargraph
- ☐ AC/DC current up to 1000A
- ☐ AC/DC voltage up to 1000V
- ☐ Display hold function
- ☐ Audible continuity test
- ☐ Overrange indication
- ☐ Frequency up to 400KHz
- ☐ Capacitance measurement
- ☐ Resistance up to 40M Ω
- ☐ Relative mode to read offset values (Zero Key)
- ☐ Peak hold for transient measurements
- ☐ Max/Min recording mode
- ☐ Confirm to the IEC-1010-1,
- ☐ UL1244/UL3111, CE standard
- ☐ Hand guard protection
- ☐ True-RMS reading
- ☐ Diode test
- ☐ Carrying case

DC voltage ranges	400mV, 4V, 40V, 400V, 1000V, $\pm$ (0.5%+1dgt)
AC voltage ranges	True RMS 400mV, 4V, 40V, 400V, 750V, $\pm$ (1.5%+4dgt)
AC current ranges	True RMS 400A, 1000A, $\pm$ (1.5%+5dgt)
DC current ranges	400A, 1000A, $\pm$ (1.5%+5dgt)
Resistance ranges	400 Ω , 4K Ω , 40K Ω , 400K Ω , 4M Ω , 40M Ω , $\pm$ (1%+2dgt)
Frequency ranges	100, 1K, 10K, 100K, 400KHz, $\pm$ (0.5%+3dgt)
Continuity test	Audible indication 400 Ω , threshold <40 Ω
General	
Power requirement	9V Battery x1
Dimension	275x90x43mm (10.8"x3.6"x1.7")
Weight	17 oz(482g)
Accessories	Test leads, soft carrying case, battery and owners manual.

conductor jaw size : 57mm